

ITE			HEALTHCARE					Gallium Nitride
Plugtop 5-24W	18-90W	120W-250W	Plugtop 12-40W	30-120W	160-300W	120-300W		
 EPA05 • 5-7.5 Watts • UK: 2.20" x 1.93" x 2.80" • Level VI & Tier 2 • PSE, RCM & BSMI • EN55032 level B	 EDA18 • 15-19 Watts • Class I: 3.94" x 1.97" x 1.3" • Class II: 3.46" x 1.97" x 1.3" • Level VI & Tier 2 • PSE, CCC, RCM & BSMI	 EDA120 • 108-120 Watts • 6.61" x 2.59" x 1.53" • DoE Level VI ErP Stage 2 • Class I • PSE, BSMI	 MPA12 • 6-12 Watts • From 3.16" x 1.8" x 1.6" • Class II • Removeable blade option • IEC60950 & IEC60601-1	 MDT30 • 20-30 Watts • 4.21" x 1.85" x 1.17" • Class II • C18 or C8	 MDA160 • 150-160 Watts • 7.2" x 3.19" x 1.65" • Single outputs 12 to 48V • IEC60601-1-2 • CoC tier 2 and ErP stage 2	 GDA120 • 108-120 Watts • 5.2" x 2" x 1.26" • Exceptional small size • Single outputs 12 to 56V • Class I (C14 or C6)		
 EPA12 • 6-12 Watts • UK: 2.83" x 1.97" x 2.80" • Level VI & Tier 2 • PSE, CCC, RCM & BSMI • EN55032	 EDA24 • 20-24 Watts • Class I: 3.94" x 1.97" x 1.3" • Class II: 3.46" x 1.97" x 1.3" • Level VI & Tier 2 • PSE, CCC, RCM & BSMI	 EDT150 • 150 Watts • 6.61" x 3.06" x 1.78" • DOE Level VI • ErP Stage 2 / CoC tier 2 • Class I or II	 MPT15 • 7-15 Watts • From 2.36" x 1.71" x 1.6" • Class II • Removeable blades • IP22	 MDA36 • 25-36 Watts • 3.94" x 1.97" x 1.3" • Class I & II models • IEC60950 & IEC60601-1 • DoE VI & ErP tier 2	 MDA200 • 192-200 Watts • 8.03" x 3.19" x 1.67" • IEC60601-1-2 • Class I & II models • DoE VI & ErP tier 2	 GDA160 • 150-160 Watts • From 5.9" x 2.12" x 1.3" • Exceptional small size • Single outputs 12 to 56V • Class I (C14/C6) or II (C8)		
 EPA18 • 15-19 Watts • UK: 2.83" x 1.97" x 3.19" • Level VI & Tier 2 • Changeable blade option • PSE, CCC, RCM & BSMI	 EDA36 • 25-36 Watts • Class I: 3.93" x 1.97" x 1.3" • Class II: 3.40" x 1.97" x 1.3" • Level VI & Tier 2 • PSE, CCC, RCM & BSMI	 EDA160 • 150-160 Watts • 6.89" x 2.91" x 1.65" • DOE Level VI • ErP Stage 2 / CoC tier 2 • Class I	 MPA20 • 17-20 Watts • From 2.72" x 2.83" x 1.34" • Class II • Removeable blades • IEC60950 & IEC60601-1	 MDT60 • 63 Watts • 5.17" x 2.18" x 1.46" • Class I & II models • EN 55011 Level B	 MDA250 • 250 Watts • 8" x 3.7" x 1.71" • Class I C14 input • MTBF 300Khrs	 GDA200 • 192-200 Watts • From 5.9" x 2.12" x 1.3" • Exceptional small size • Single outputs 12 to 56V • Class I (C14/C6) or II (C8)		
 EPA24 • 20-24 Watts • UK: 2.83" x 1.97" x 3.19" • Level VI & Tier 2 • Changeable input plugs • PSE, CCC, RCM & BSMI	 EDA65 • 60-65 Watts • 4.53" x 2.09" x 1.50" • Level VI ErP stage 2 • Class I and II • PSE, CCC, RCM & BSMI	 EDA200 • 192-200 Watts • 3.19" x 7.20" x 1.65" • Class I-C14 • Single outputs 12 to 56V • US DoE Energy efficiency level VI	 MPT26 • 16-25 Watts • From 3.66 x 1.97" x 1.55" • Class II • Removeable blade • IP22	 MDA65 • 60-65 Watts • 4.69" x 2.36" x 1.42" • IEC 60950 / IEC 60601-1 • DoC VI & ErP tier 2 • Class I / II versions	 EDM250 • 250 Watts • 7.87" x 3.54" x 1.77" • Level VI & Tier 2 • Low Profile	 GDM200 • 192-200 Watts • From 6.54" x 2.13" x 1.3" • IEC 60601-1 / IEC 60601-1-2 • Single outputs 12 to 48V • Class I (C14/C6) or II (C8)		
 EDA90 • 90 Watts • 2.51" x 5.94" x 1.42" • DoE Level VI, ErP stage 2 • BSMI, PSE • EN 55032 Class B	 EDA250 • 240-250 Watts • 3.70" x 8.30" x 1.71" • Class I-C14 • Single outputs 12 to 56V • US DoE Energy efficiency level VI	 MPT40 • 30-40 Watts • From 3.66 x 1.97" x 1.55" • Class II • Removeable blade • IP22	 MDA90 • 84-90 Watts • 6.29" x 2.51" x 1.38" • IEC 60950 / IEC 60601-1 • DoC VI & ErP tier 2 • Class I / II versions	 MDA300 • 300 Watts • 10" x 4.56" x 1.85" • Class I (C14) or II (C18) • Single outputs 12 to 48V • MTBF 300Khrs	 EDM300 • 300 Watts • 8.74" x 4.4" x 1.77" • Class I and II • DoE Level VI • Low profile	 GDM250 • 228-250 Watts • From 6.81" x 2.64" x 1.26" • IEC 60601-1 / IEC 62368-1 • Single outputs 12 to 56V • Class I (C14) or II (C18)		
				 MDA120 • 108-120 Watts • 2.59" x 6.61" x 1.53" • Single outputs 12 to 48V • Class I & II models • IEC 60601-1-2 4th Edition EMC	 EDM300 • 288-300 Watts • From 7.22" x 3.35" x 1.38" • IEC 60601-1 / IEC 62368-1 • Single outputs 12 to 56V • Class I (C14) or II (C18)	 GDM300 • 288-300 Watts • From 7.22" x 3.35" x 1.38" • IEC 60601-1 / IEC 62368-1 • Single outputs 12 to 56V • Class I (C14) or II (C18)		

Full data available at: www.fiduspower.com

Can't find what you're looking for?
Call us on 0118 342 0730

- Medical version available